



RALLON M-TEAM.

È DISPONIBILE IN QUESTI COLORI:



METALLIC MULBERRY
(GLOSS-MATT)



GOLDEN SAND-NIGHT BLACK
(MATT)



JADE GREEN CARBON
(GLOSS)-STONE SILVER
(MATT)


SPECIFICHE E OPTIONAL

TELAIO	Orbea Monocoque Race Carbon. Advanced Dynamics 160mm suspension technology. 29" wheels. Concentric Boost 12x148 rear axle. Pure Enduro geometry. Internal cable routing. ISCG05
AMMORTIZZATORE	Fox Float X2 Factory 2-Position Adjust Kashima custom tune 230x60mm
	Fox DHX2 Factory 2-Pos Adjust SLS Spring Cr 230x60mm 400lbs
	Fox DHX2 Factory 2-Pos Adjust SLS Spring Cr 230x60mm 450lbs
	Fox DHX2 Factory 2-Pos Adjust SLS Spring Cr 230x60mm 500lbs
	Fox DHX2 Factory 2-Pos Adjust SLS Spring Cr 230x60mm 550lbs
FORCELLA	Fox 38 Float Factory 170 Grip2 QR15x110 Kashima
GUARNITURA	Race Face Next-R 32t
SERIE STERZO	Acros Alloy 1-1/8 - 1-1/2" Integrated
MANUBRIO	Race Face Next R 35 20mm Rise 800mm
ATTACCO	Race Face Turbine R 35mm interface
LEVE	Shimano XT M8100 I-Spec EV
FRENI	Shimano XT M8120 Hydraulic Disc Shimano XTR M9120 Hydraulic Disc
PIGNONI	Shimano CS-M8100 10-51t 12-Speed
CAMBIO	Shimano XT M8100 SGS Shadow Plus
CATENA	Shimano M7100
RUOTE	Race Face TURBINE-R 30 TLR IS (29" Front / 27,5" Rear) Race Face TURBINE-R 30 TLR IS
PNEUMATICO	Maxxis Assegai 2.50" WT FB 120 TPI 3C Maxx Terra EXO+ TR
PNEUMATICO	Maxxis Minion DHR II 2.40" WT FB 120 TPI 3C Maxx Terra EXO+ TR
REGGISELLA	Fox Transfer Factory Kashima Dropper 31.6 Fox Transfer Factory Kashima Dropper 31.6x363,5/125mm Fox Transfer Factory Kashima Dropper 31.6x418,3/150mm Fox Transfer Factory Kashima Dropper 31.6x475/175mm Fox Transfer Factory Kashima Dropper 31.6x530,7/200mm
REMOTO REGGISELLA	Shimano SL-MT500 I-Spec EV
SELLA	Fizik Taiga Kium rail
TENDICATENA	e*thirteen CL52 30-36t black
BLOQUEO ANTERIORE	Fox Kabolt Boost
PORTA ATTREZZI	Accessories Containers
STRUMENTI	OC axle lever (Hex 6 & valve core removal) + OC Multitool (Hex 2, 3, 4 & 5)

GEOMETRIA

TAGLIA	S H/L	M H/L	L H/L	XL H/L	S-MT	M-MT	L-MT	XL-MT
1 - SEAT_TUBE	415	415	435	460	415	415	435	460
2 - TOP_TUBE	572	599	626	653	573	600	627	655
3 - HEAD_TUBE	90	100	110	120	90	100	110	120
4 - CHAIN_STAY	440	440	440	440	438	438	438	438
5 - BB_HEIGHT*	343/336	343/336	343/336	343/336	343	343	343	343
6 - BB_DROP*	28/35	28/35	28/35	28/35	35	35	35	35
7 - WHEELBASE	1202	1231	1260	1290	1201	1230	1260	1289
8 - HEAD_ANGLE*	64,5°/64°	64,5°/64°	64,5°/64°	64,5°/64°	64°	64°	64°	64°
9 - SEAT_ANGLE*	77,5°/77°	77,5°/77°	77,5°/77°	77,5°/77°	77°	77°	77°	77°
10 - STANDOVER	737	737	754	774	744	744	761	781
11 - REACH	435	460	485	510	430	455	480	505
12 - STACK	619	628	637	646	623	632	641	650
13 - FORK_LENGTH	587,7							

*



ERGONOMIA

TAGLIA	BIELLA	ATTACCHO	MANUBRIO	REGGISELLA TELESCOPICO
S	170	40	800	418/150
M	170	40	800	418/150
L	170	50	800	475/175
XL	170	50	800	530,7/200

* La misura del manubrio è centro-Centro